

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-271037

(43)Date of publication of application : 02.10.2001

(51)Int.Cl.

C09J 4/02
C08F 2/44
C08F 20/00
C08F279/02
C09J 11/04
C09J201/00

(21)Application number : 2000-086695

(71)Applicant : DENKI KAGAKU KOGYO KK

(22)Date of filing : 27.03.2000

(72)Inventor : SAKURAI TETSUYA
MIHARA HIDEHIRO
TAGUCHI KOICHI

(54) FLAME-RETARDED RESIN COMPOSITION, FLAME-RETARDED ADHESIVE
COMPOSITION AND METALLIC JUNCTION FORM

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a flame-retarded resin composition and a flame-retarded adhesive composition each seldom affecting human health or the environment and excellent in flame retardancy, adhesion and moisture resistance.

SOLUTION: This flame-retarded resin composition or flame-retarded adhesive composition comprises (1) a polymerizable vinyl monomer, (2) a polymerization initiator, (3) a reducing agent, (4) a phosphate salt and (5) a metal hydroxide, and also may contain (6) an elastomer component.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office

JAPANESE [JP,2001-271037,A]

[Translation done.]

CLAIMS DETAILED DESCRIPTION TECHNICAL
FIELD PRIOR ART EFFECT OF THE INVENTION
TECHNICAL PROBLEM MEANS EXAMPLE

[Translation done.]

*** NOTICES ***

Japan Patent Office is not responsible for any
damages caused by the use of this translation.

- 1.This document has been translated by computer.
So the translation may not reflect the original
precisely.
- 2.**** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

[Claim 1] (1) The fire-resistant adhesives
constituent which comes to contain a
polymerization nature vinyl monomer, (2)
polymerization initiators, (3) reducing agents, (4)
phosphate, and (5) metal hydroxide.

[Claim 2] Furthermore, the flame-retardant-resin
constituent according to claim 1 which comes to
contain (6) elastomer component.

[Claim 3] (1) The flame-retardant-resin constituent
according to claim 1 or 2 whose polymerization
nature vinyl monomer is a polymerization nature
(meta) acrylic-acid derivative.

[Claim 4] a flame-retardant-resin constituent given
[of the claims 1-3] in one term -- the [a first
agent and] -- the 2 pharmaceutical-form flame-
retardant-resin constituent with which it divides
into 2 agents, a first agent comes to contain a
polymerization initiator at least, and the second
agent comes to contain a reducing agent at least
[Claim 5]

Copyright (C); 2000 Japan Patent Office

JAPANESE

[JP,2001-271037,A]

CLAIMS DETAILED DESCRIPTION TECHNICAL FIELD PRIOR ART EFFECT OF THE
INVENTION TECHNICAL PROBLEM MEANS EXAMPLE

[Translation done.]

* NOTICES *

Japan Patent Office is not responsible for any damages caused by the use of this translation.

- 1.This document has been translated by computer. So the translation may not reflect the original precisely.
- 2.*** shows the word which can not be translated.
- 3.In the drawings, any words are not translated.

CLAIMS

[Claim(s)]

[Claim 1] (1) The fire-resistant adhesives constituent which comes to contain a polymerization nature vinyl monomer, (2) polymerization initiators, (3) reducing agents, (4) phosphate, and (5) metal hydroxide.

[Claim 2] Furthermore, the flame-retardant-resin constituent according to claim 1 which comes to contain (6) elastomer component.

[Claim 3] (1) The flame-retardant-resin constituent according to claim 1 or 2 whose polymerization nature vinyl monomer is a polymerization nature (meta) acrylic-acid derivative.

[Claim 4] a flame-retardant-resin constituent given [of the claims 1-3] in one term -- the [a first agent and] -- the 2 pharmaceutical-form flame-retardant-resin constituent with which it divides into 2 agents, a first agent comes to contain a polymerization initiator at least, and the second agent comes to contain a reducing agent at least

[Claim 5] The fire-resistant adhesives constituent which consists of a flame-retardant-resin constituent given [of the claims 1-4] in one term.

[Claim 6] The hardening field of a flame-retardant-resin constituent given [of the claims 1-4] in one term.

[Claim 7] The metal zygote which it comes to join with a fire-resistant adhesives constituent according to claim 5.

[Translation done.]

本願に先行する関連出願特許データ(5/5)

特許出願 2000- 86695[H12. 3.27] 請求() 出願種別 (通常)

特開 2001-271037[H13.10. 2]

名称 難燃性樹脂組成物、難燃性接着剤組成物及び金属接合体

出願人 13-000329 電気化学工業 (株)

発明者 桜井 哲也,三原 英裕,田口 広一

I P C C09J 4/02 C08F 2/44 C08F 2/44

C08F 20/00 C08F279/02 C09J 11/04

C09J201/00

代理人 () 他()

優先権 () [] () [] ()

関連種別 () 原出願番号 () 原登録番号 ()

基準日 (出願日) [平 12. 3.27] 遡及日 [] ()

審査異議有効数 () 請求項の数 (007) 権利譲渡／実施許諾 ()

査定種別 (-) [] 最終処分 () []

審査種別 (通常審査)

審査記録 (A63 願書 ,平 12. 3.27,21000:)

(A967 認定情報,平 12. 3.29, :)

【整理番号】 A088940
特願2000-86695 (H12. 3. 27)
特開2000-271037 (H13. 10. 2)

【発明の名称】 難燃性樹脂組成物、難燃性接着剤組成物及び金属接合体

【特許請求の範囲】

【請求項1】 (1) 重合性ビニルモノマー、(2) 重合開始剤、(3) 還元剤、
(4) リン酸塩及び(5) 金属水酸化物を含有してなる難燃性接着剤組成物。

【請求項2】 さらに、(6) エラストマー成分を含有してなる請求項1記載の難燃性樹脂組成物。

【請求項3】 (1) 重合性ビニルモノマーが重合性(メタ)アクリル酸誘導体である請求項1又は2記載の難燃性樹脂組成物。

【請求項4】 請求項1～3のうちの1項記載の難燃性樹脂組成物を第一剤及び第二剤に分け、第一剤が少なくとも重合開始剤を含有してなり、第二剤が少なくとも還元剤を含有してなる二剤型難燃性樹脂組成物。

【請求項5】 請求項1～4のうちの1項記載の難燃性樹脂組成物からなる難燃性接着剤組成物。

【請求項6】 請求項1～4のうちの1項記載の難燃性樹脂組成物の硬化体。

【請求項7】 請求項5記載の難燃性接着剤組成物により接合してなる金属接合体。